



## COMPETITION COMPENSATOR

- 4" TACTICAL RAIL
- 2" TACTICAL RAIL
- HAND GUARD BRACE
- QD SLING MOUNT

### PARTS INCLUDED

JPTR-L/LRC	JPTR-S/SRC	JPHGB/RC	JPHG-SM/-RC
<ul style="list-style-type: none"> <li>• Four-inch rail piece</li> <li>• Three (3) 10-32 flat socket cap screws</li> <li>• Backer plate (JPTR-L only)</li> </ul>	<ul style="list-style-type: none"> <li>• Two-inch rail piece</li> <li>• Two (2) 10-32 flat socket cap screws</li> <li>• Backer plate (JPTR-S only)</li> </ul>	<ul style="list-style-type: none"> <li>• Hand guard brace</li> <li>• Two (2) 10-32 flat socket cap screws</li> <li>• Backer plate (JPHGB only)</li> </ul>	<ul style="list-style-type: none"> <li>• Sling mount</li> <li>• Two (2) 10-32 flat socket cap screws</li> <li>• Backer plate (JPHG-SM only)</li> </ul>

**CAUTION: REMOVE MAGAZINE AND VISUALLY CHECK CHAMBER TO MAKE SURE THAT FIREARM IS UNLOADED.**

The JP MK III Hand Guard System system allows for complete flexibility of accessory placement on the outside of your hand guard tube. Any rail or accessory can be mounted in a variety of applications while still keeping the overall weight of the forend to a minimum. These components are specially designed for JP MK III and previous generation hand guard tubes but are compatible with many other free float tubes.

For use on the slotted Signature hand guard tubes, place the backer plate in the desired slot on the inside of the tube. It may help to use a small hex key or knife blade inserted though the adjacent slots in the tube to keep the slot piece in place while you inert the screws.

For attachment on Rapid Configuration tubes, attach the rail or accesory directly to the tube using the supplied 10-32 flat head screws. Tighten all screws to 5-6 in-lbs.

In the case of rails, note that the segments have multiple holes for flexibility. Only one of the 10-32 flat head screws is actually needed to lock the rail into position.

**THANKS FOR YOUR BUSINESS!**